
Environmentally Friendly Coating Systems for Department of Defense Applications

Nathan Silvernail, Ph.D.
PPG Industries, Inc.


U.S. Army Corrosion Summit
Huntsville, Alabama
February 9-11, 2010



VIEWS, OPINIONS, AND/OR FINDINGS CONTAINED IN THIS REPORT ARE THOSE OF THE AUTHOR AND SHOULD NOT BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF DEFENSE POSITION OR DECISION UNLESS SO DESIGNATED BY OTHER OFFICIAL DOCUMENTATION.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE FEB 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010	
4. TITLE AND SUBTITLE Environmentally Friendly Coating Systems for Department of Defense Applications				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) PPG Industries, Inc,One PPG Place,Pittsburgh,PA,15272				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES U.S. Government or Federal Rights License					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 25	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Evaluation of New Technologies



Programs

E-Coat for Munitions Modernization



Environmentally Friendly Zirconium Oxide Pretreatment




SERDP WP-1676

E-Coat for Munitions Modernization



ARDEC Personnel

Jules Senske
Dan Schmidt
Don Skelton




<http://www.theodoregray.com/PeriodicTable/>

- “Electrocoat for Munitions Modernization”
 - Jules Senske, U.S. ARMY Corrosion Summit, 13 February 2008
- Coatings for munitions modernization
 - Project originally targeted acrylic electrocoat development
 - Expanded to powder coatings and other environmentally friendly treatments for munitions applications

Coatings for Munitions Modernization


- Current commercial munitions coatings

- Alkyd Enamels (Mil-E-52891, Mil-DTL-11195)
- Applied by spray or dip process
- Salt-spray resistance requirement, 150 hrs
- Possible aesthetic drawbacks (runs, drips, sags, etc.)




- Coatings for munitions modernization

- Acrylic electrocoat and polyurethane powder
- Higher work efficiency/simplified process
- Durability > 750 WOM
- Salt-spray resistance > 400 hrs
- High transfer efficiency (approach 95-100%)
- Low or no VOC
- Widely used industrially



500 hrs neutral salt spray




Coatings for Munitions Modernization (Systems Approach)




- Development of complementary coating systems for munitions applications
 - Opportunity to evaluate E-Coat and powder on munitions substrates
 - Systems approach for asset protection and enhancement
 - Aluminum, magnesium, and titanium
 - Stainless steel and high-strength steel (armor applications)

Systems Approach (Commercial Pretreatments with Powder Coating)


GM9540P, 20 cycles




- Cold-rolled steel
- 2 mil Polyurethane powder coating
- Pretreated samples had < 1/4" scribe creep after 20 cycles GM9540P





Systems Approach (Commercial Pretreatments with Powder Coating)




- Cold-rolled steel
- 2 mil Polyurethane powder coating
- Pretreated samples had < 1/4" scribe creep after 400 Salt-Spray



Systems Approach (Commercial Pretreatments with Powder Coating)




Systems Approach (Commercial Pretreatments with Powder Coating)



- 2 mil film build specification for polyurethane powder coatings
- ZrOx outperforms commercial Zn Phosphate
- Scribe creep specification met at all film thicknesses for ZrOx

Systems Approach (Commercial Pretreatments with Powder Coating)



- 2 mil film build specification for polyurethane powder coatings
- Better adhesion at all coating thicknesses for the ZrOx pretreatment

Systems Approach (Commercial Pretreatments with Powder Coating)

- Conclusions
 - Polyurethane powder/commercial pretreatment coating systems perform well in the testing outlined in Mil-E-52891 and Mil-DTL-11195, with several added environmental benefits over alkyd systems.
 - The powder/commercial zirconium pretreatment system provides performance superior to Zn phosphate, in adhesion and corrosion testing (ASTM B117 and GM9540P), at lower applied powder thickness.
- Path forward
 - Pretreatment systems for Ti, Mg, and Al alloys
 - Study the electrocoat system with commercial ZrOx pretreatments


Environmentally Friendly Zirconium Oxide Pretreatment




SERDP WP-1676




ARL Personnel
John Escarsega
Fred Lafferman
Daniel Pope
Pauline Smith



Do We Need Pretreatment?



No pretreatment



Zinc phosphate pretreatment

Electrocoated steel panels after GM 9540 cyclic corrosion testing

Environmentally Friendly Zirconium Oxide Pretreatment

Environmental/Health Impact


- DoD Wash Primer systems
 - 7.1% zinc chromate
 - 6.5 lb/gal of VOCs
- Yearly est. usage of 21,000 gal
 - 12,600 lb of zinc chromate
 - 35,700 gal of package/thinner solvents
- Environmental concerns and EPA regulatory issues associated with solvent emissions
- Worker safety and OSHA compliance issues related to the presence of regulated metals



Environmentally Friendly Zirconium Oxide Pretreatment

Wash Primer/Pretreatment

- Chemical Agent Resistant Coating (CARC) specification, MIL-C-53072, requires metal surfaces be treated to improve coating adhesion and corrosion resistance
- Zinc phosphate pretreatment required for Original Equipment Manufacturers
- Hexavalent Chrome (Cr^{6+}) containing wash primer required for Depot and Repair operations



SERDP 1676 Project Objective


- Develop an environmentally friendly pretreatment system for multi-material DoD applications
 - Free of hexavalent chromium (Cr^{6+})
 - No volatile hazardous air pollutants (HAPs)
 - Ease of application using existing infrastructure
 - Equal or better corrosion performance to current (Cr^{6+}) wash primers
 - Broad substrate/topcoat compatibility
 - Cost effective

Zirconium-Based Pretreatments


- Commercial Zirconium-Based Pretreatment
 - No regulated metals in pretreatment
 - Reduced energy cost for pretreatment application
 - Reduced water consumption for pretreatment application
 - Reduced pretreatment waste
 - No HAPS or VOC in pretreatment system
- Do commercial zirconium-based immersion pretreatments meet DoD specifications?
 - Confirm/determine that existing formulas meet DoD standards
 - Modify to meet DoD needs as necessary
 - Early experiments suggest Automotive OEM formula may not be directly applicable to DoD substrates/coating systems

Environmentally Friendly Zirconium Oxide Pretreatment

Task 1: OEM Pretreatment Development



immersion-applied ZrOx




spray-applied ZrOx

Task 3: Repair Pretreatment Development



- Sanding
- Spray-Gun applied
- Wand applied
- Wipe-on

Task 2: Depot Pretreatment Development



Environmentally Friendly Zirconium Oxide Pretreatment

Task 1: OEM Pretreatment Development



immersion-applied ZrOx



spray-applied ZrOx

- Evaluate commercial immersion formulae with DoD substrates and coatings - reformulate as needed (Mil-Spec testing at ARL).
- Investigate and optimize lab prototype formula with a range of spray application conditions (Mil-Spec testing at ARL).

Environmentally Friendly Zirconium Oxide Pretreatment

- Visit DoD depot facilities to benchmark application process/conditions
- Determine compatibility of OEM spray formula with depot equipment.
- Characterization and limited Mil-Spec testing
- Formula optimization
- Comprehensive Mil-Spec testing

Task 2: Depot Pretreatment Development



Environmentally Friendly Zirconium Oxide Pretreatment

- Surface characterization.
- Evaluate optimized ZrOx spray formulation
- Limited Mil-Spec testing
- Reformulate
- Characterize
- Comprehensive Mil-Spec testing

Task 3: Repair Pretreatment Development



- Sanding
- Spray-Gun applied
- Wand applied
- Wipe-on

Acknowledgements



PPG Industries

Ed Abbott
Scott Benton
Bob Lipinski
Maggie MacKay
Michael Pawlik
Jim Poole
Ed Rakiewicz
Mike Sandala



ARDEC

Jules Senske
Dan Schmidt
Don Skelton



ARL

John Escarsega
Fred Lafferman
Daniel Pope
Pauline Smith



SERDP

Bruce Sartwell
Jeffery Houff
Caitlin Rohan

Questions?

E-mail:
nsilvernail@ppg.com

Zirconium-Based Pretreatment

